ouble Hi





energyWall® energyWELD® Double Hung Window




Limit Lock Reliable Limit Lock

securing a partial opening for safety.



Innovative

Intuitive functionality enables latch to operate with a swing of the lock lever.



Streamlined

Sleek lock visuals provide high-end appearance and market distinction.



Latch and Lock hold hundreds of pounds of static loading.




1. DuoTilt engaged allowing sash to til in for cleaning.



2. Lever in this position unlocks the window allowing you to open



3. Lock engaged to ensure secure closure.



DuoTilt lock standard on all

DuoTilt

Featuring

Lock

Innergy ® standard

Innergy is the innovative, energy-efficient alternative to aluminum. Rigid
Thermal Reinforcements are advanced fiberglass reinforced resin inserts, designed to slide easily into window and door frame chambers for greater support and insulation.





- Better Thermal Performance
 Up to 700 times better than
 aluminum in material-to-material
 comparisons.
- Better Thermal Break Impervious to cold or heat.
- Better protection against condensation
 Helps prevent staining that can occur with metal reinforcements.
- Better flexibility
 Will not permanently set
 when impacted.







Partner

NAMI Certified


BLACK Intercept Stainless standard

Sealant Effectiveness & Gas Retention. The sealant provides the moisture vapor barrier for the I.G. unit. The longer the transmission path, the slower the rate that moisture will travel into the unit through the seal. STAINLESS Steel is Impervious to gas transmission, improving gas retention and Maximizing the insulation value of your window over time. Intercept® Stainless offers one of the best transmission paths to maximize window performance.




FOAM fill

standar



Foam Fill in Head.

Weather Stripping



Foam Fill in Sill.

Sill Bulb

Weather Stripping

Structural Sill Interlock